



**Omega sékli G-4161 típus**


Biztonsági tényező: 6. Galvanizált. Menetes csappal.



Típus	Teherbírási (kg)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	Tömeg (kg/db/m)	Megr. sz.
G4161-1/4	500	7	8	12	29	20	0.06	3011001
G4161-5/16	750	9	10	13.5	32	21	0.11	3011003
G4161-3/8	1000	10	11	16.1	36	26	0.15	3011005
G4161-7/16	1500	11	13	18	43	29	0.21	3011007
G4161-1/2	2000	13	16	22	51	32	0.37	3011009
G4161-5/8	3250	16	19	27	64	43	0.65	3011011
G4161-3/4	4750	19	22	31	76	51	1.06	3011013
G4161-7/8	6500	22	25	36	83	58	1.56	3011015
G4161-1	8500	25	28	43	95	68	2.32	3011017
G4161-1.1/8	9500	28	32	47	108	75	3.28	3011018
G4161-1.1/4	12000	32	35	51	115	83	4.51	3011019
G4161-1.3/8	13500	35	38	57	133	92	5.93	3011020
G4161-1.1/2	17000	38	42	60	146	99	7.89	3011021
G4161-3/4	25000	45	50	74	178	126	13.4	3011023
G4161-2	35000	50	57	83	197	138	18.15	3011025
G4161-2.1/4	42500	57	65	95	222	160	26.29	3011027
G4161-2.1/2	55000	65	70	105	260	180	37.6	3011029


**U-alakú sékli G-4163 típus**

Biztonsági tényező: 6. Galvanizált. Sásszeg-furatatos anyás csavarral.



Típus	Teherbírási (kg)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	Tömeg (kg/db/m)	Megr. sz.
G4163-1/4	500	7	8	12	29	20	0.06	3012001
G4163-5/16	750	9	10	13.5	32	21	0.11	3012003
G4163-3/8	1000	10	11	16.1	36	26	0.15	3012005
G4163-7/16	1500	11	13	18	43	29	0.21	3012007
G4163-1/2	2000	13	16	22	51	32	0.37	3012009
G4163-5/8	3250	16	19	27	64	43	0.65	3012011
G4163-3/4	4750	19	22	31	76	51	1.06	3012013
G4163-7/8	6500	22	25	36	83	58	1.56	3012015
G4163-1	8500	25	28	43	95	68	2.32	3012017
G4163-1.1/8	9500	28	32	47	108	75	3.28	3012018
G4163-1.1/4	12000	32	35	51	115	83	4.51	3012019
G4163-1.3/8	13500	35	38	57	133	92	5.93	3012020
G4163-1.1/2	17000	38	42	60	146	99	7.89	3012021
G4163-1.3/4	25000	45	50	74	178	126	13.4	3012023
G4163-2	35000	50	57	83	197	138	18.15	3012025
G4163-2.1/4	42500	57	65	95	222	160	26.29	3012027
G4163-2.1/2	55000	65	70	105	260	180	37.6	3012029